

## Garant

### Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC m6: 13/32 mm or inch



#### Order data

Order number	123212 13/32
GTIN	4062406116323
Item class	11E

#### Description

##### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

##### Recommendation:

##### Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068– 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form **HB**: with **No. 123214**.

Order form **HE**: with **No. 123212 + 129100HE**.

Machining strategy: HPC

Standard: Manufacturer's standard

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: m6

recommended maximum drilling depth  $L_2$ : 140.3 mm

Overall length L: 204 mm

Shank Ø  $D_s$ : 12 mm

Feed f in stainless steel > 900 N/mm<sup>2</sup>: 0.15 mm/rev.

## Technical description

Tolerance nominal $\varnothing$	m6
Flute length $L_c$	156 mm
Shank tolerance	h6
Overall length L	204 mm
Standard	Manufacturer's standard
Shank $\varnothing D_s$	12 mm
Number of cutting edges Z	2
Inch nominal $\varnothing$ corresponds to	10.32 mm
recommended maximum drilling depth $L_2$	140.3 mm
Feed f in stainless steel > 900 N/mm <sup>2</sup>	0.15 mm/rev.
Semi-Standard	yes
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	12xD
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	blue
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------