

Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, \varnothing DC m6: 5/8 mm or inch



Order data

Order number	123212 5/8
GTIN	4062406116385
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers.** Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For process reliability when using the 12×D drill, an initial centre drilling with NC spotting drills No. 121068– 121130 is necessary.

Form HB and HE are supplied at the same price as HA.

Order form HB: with No. 123214.

Order form **HE:** with **No. 123212 + 129100HE**.

Machining strategy: HPC

Standard: Manufacturer's standard

Tolerance nominal Ø: m6 Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: m6

recommended maximum drilling depth L₂: 184 mm

Overall length L: 260 mm Shank Ø D_s: 16 mm

Feed f in stainless steel > 900 N/mm²: 0.2 mm/rev.

Technical description

Inch nominal Ø corresponds to	15.88 mm
Shank tolerance	h6
Overall length L	260 mm
recommended maximum drilling depth L_2	184 mm
Standard	Manufacturer's standard
Flute length L _c	208 mm
Number of cutting edges Z	2
Tolerance nominal Ø	m6
Shank Ø D _s	16 mm
Feed f in stainless steel > 900 N/mm ²	0.2 mm/rev.
Semi-Standard	yes
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	12×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	blue
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------