Garant

GARANT Master Steel DEEP solid carbide pilot drill, plain shank DIN 6535 HA 6×D, TiAIN, Ø DC: 14 mm

Order data

Order number	123885 14
GTIN	4062406267582
Item class	11E

Description

Version:

Excellent chip evacuation due to the unequal helical pitch of the flutes, guide rings and additional guide chamfers for very high precision when drilling. Maximum process reliability due to exactly matching tools within the overall system. Drilling up to the maximum depth without a pilot drill. Significantly increased tool stability due to the substantially strengthened core. Increased metal removal rates and outstanding tool lives lead to an economical highend drilling process.

Strong core and special point geometry for high centring accuracy. 140° tip angle and special p6 cutting tolerance for optimum generation of a pilot hole for subsequent use of the GARANT Master Steel deep hole drill.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$. Note: Flute length $L_c = L_2 + 1.5 \times D_c$. Form HB and HE supplied at the same price as HA. Form **HB:** order with **No. 123886**. Form **HE:** order with **No. 123885 + 129100HE**. Standard: Manufacturer's standard Tolerance nominal Ø: p6 Number of cutting edges Z: 2

Tolerance nominal Ø: p6 Overall length L: 124 mm

Shank Ø D_s: 14 mm

Feed f in steel < 900 N/mm²: 0.29 mm/rev.

Technical description

Standard	Manufacturer's standard
Shank Ø D _s	14 mm
Overall length L	124 mm
Nominal Ø D _c	14 mm
Tolerance nominal Ø	рб
Flute length L _c	77 mm
Number of cutting edges Z	2
Feed f in steel < 900 N/mm ²	0.29 mm/rev.
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	16×D
Point angle	138 degrees
Shank	DIN 6535 HA to h5
Through-coolant	yes, with 40 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Type of product	Jobber drill