

Garant
GARANT Master Steel DEEP solid carbide deep-hole drill, plain shank DIN 6535 HA 16×D, TiAlN, Ø DC: 3 mm

Order data

Order number	123888 3
GTIN	4062406263003
Item class	10E

Description
Version:

Excellent chip evacuation due to the unequal helical pitch of the flutes, guide rings and additional guide chamfers for very high precision when drilling. **Maximum process reliability** due to exactly matching tools within the overall system. Drilling up to the maximum depth without a pilot drill. **Significantly increased tool stability** due to the substantially strengthened core. **Increased metal removal rates** and **outstanding tool lives** lead to an economical high-end drilling process.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

For process reliability when using the 16×D deep-hole drill, an initial centre drilling with No. 121068 – 121130 or at least 4×D pilot drilling operation with pilot drill No. 123885 is necessary. For deep holes greater than 20×D, a pilot hole to the maximum drilling depth with pilot drill No. 123885 is absolutely essential. The generation of a pilot hole improves process reliability. **The specified L/D ratio gives the minimum achievable depth of hole with the respective deep-hole drill.**

Flute length $L_c = L_2 + 1.5 \times D_c$.

Standard: Manufacturer's standard

Tolerance nominal Ø: j6

Number of cutting edges Z: 2

Tolerance nominal Ø: j6

recommended maximum drilling depth L_2 : 55.5 mm

Overall length L: 103 mm

Shank Ø D_s : 6 mm

Feed f in steel < 900 N/mm²: 0.07 mm/rev.

Technical description

recommended maximum drilling depth L_2	55.5 mm
Feed f in steel $< 900 \text{ N/mm}^2$	0.07 mm/rev.
Tolerance nominal $\varnothing$	j6
Number of cutting edges Z	2
Flute length L_c	60 mm
Overall length L	103 mm
Shank $\varnothing D_s$	6 mm
Nominal $\varnothing D_c$	3 mm
Standard	Manufacturer's standard
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	16xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 40 bar
Machining strategy	HPC
Pilot drill required	yes, pilot drill
Colour ring	green
Type of product	Jobber drill