

Garant
Through hole machine tap, uncoated, M: M17X0,35

Order data

Order number	130000 M17X0,35
GTIN	4045197998514
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 2 pcs.
 Special / custom-made product - return not possible
 Thread type: M/MF
 Tool material: HSS E
 Standard: DIN 376
 Thread pitch: 0.35 mm
 Overall length L: 125 mm
 Shank $\varnothing D_s$: 14 mm
 Shank square \square : 11 mm
 Tapping hole \varnothing : 16.65 mm

Technical description

Overall length L	125 mm
Shank $\varnothing D_s$	14 mm
Tool material	HSS E
Number of clamping slots	3
Tapping hole \varnothing	16.65 mm
Thread \varnothing	17 mm
Number of cutting edges Z	3
Thread depth	34 mm

Standard	DIN 376
Thread pitch	0.35 mm
Shank square <input type="checkbox"/>	11 mm
Thread type	M/MF
Thread size	M17×0.35
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap