

Garant**Through hole machine tap, uncoated, M: M2X0,35****Order data**

Order number	130000 M2X0,35
GTIN	4045197997593
Item class	10N

Description**Note:**

Delivery time: 91 calendar days

Minimum order quantity: 25 pcs.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 371

Thread pitch: 0.35 mm

Overall length L: 45 mm

Shank Ø D_s: 2.8 mm

Shank square □: 2.1 mm

Tapping hole Ø: 1.65 mm

Technical description

Tool material	HSS E
Overall length L	45 mm
Shank Ø D _s	2.8 mm
Standard	DIN 371
Tapping hole Ø	1.65 mm
Number of clamping slots	3
Shank square □	2.1 mm
Thread depth	4 mm

Thread Ø	2 mm
Thread pitch	0.35 mm
Number of cutting edges Z	3
Thread type	M/MF
Thread size	M2×0.35
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap