Garant

Through hole machine tap, uncoated, MF: M36X0,5



Order data

Order number	130000 M36X0,5
GTIN	4045197000026
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 1 pc.
Special / custom-made product - return not possible
Thread type: M/MF
Tool material: HSS E
Standard: DIN 376
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 0.5 mm
Overall length L: 200 mm
Shank ⌀ D_s: 28 mm
Shank square ☐: 22 mm
Tapping hole ⌀: 35.5 mm

Technical description

Shank square ☐	22 mm
Tapping hole ⌀	35.5 mm
Thread pitch	0.5 mm
Shank ⌀ D_s	28 mm
Overall length L	200 mm
Number of cutting edges Z	4

Standard	DIN 376
Tool material	HSS E
Number of clamping slots	4
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tolerance class	6H +0.20
Thread ∅	36 mm
Thread depth	72 mm
Thread type	M/MF
Thread size	M36×0.5
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap