Garant

Through hole machine tap, uncoated, M: M37X0,35



Order data

Order number	130000 M37X0,35
GTIN	4045197625694
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 1 pc.
Special / custom-made product - return not possible
Thread type: M/MF
Tool material: HSS E
Standard: DIN 376
Thread pitch: 0.35 mm
Overall length L: 200 mm
Shank ⌀ D_s: 32 mm
Shank square ☐: 24 mm
Tapping hole ⌀: 36.65 mm

Technical description

Standard	DIN 376
Thread pitch	0.35 mm
Overall length L	200 mm
Shank square ☐	24 mm
Thread ⌀	37 mm
Number of clamping slots	4
Shank ⌀ D_s	32 mm
Thread depth	74 mm

Tool material	HSS E
Tapping hole ∅	36.65 mm
Number of cutting edges Z	4
Thread type	M/MF
Thread size	M37×0.35
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap