

Garant
Through hole machine tap, uncoated, M: M38X0,75

Order data

Order number	130000 M38X0,75
GTIN	4045197625021
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: M/MF
 Tool material: HSS E
 Standard: DIN 376
 Thread pitch: 0.75 mm
 Overall length L: 200 mm
 Shank \varnothing D_s: 32 mm
 Shank square \square : 24 mm
 Tapping hole \varnothing : 37.25 mm

Technical description

Thread \varnothing	38 mm
Number of cutting edges Z	4
Overall length L	200 mm
Standard	DIN 376
Number of clamping slots	4
Shank square \square	24 mm
Thread depth	76 mm
Tool material	HSS E

Shank $\varnothing D_s$	32 mm
Tapping hole \varnothing	37.25 mm
Thread pitch	0.75 mm
Thread type	M/MF
Thread size	M38 \times 0.75
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3 \times D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap