

Garant
Through hole machine tap, uncoated, M: M4X0,7

Order data

| | |
|--------------|---------------|
| Order number | 130000 M4X0,7 |
| GTIN | 4045197997760 |
| Item class | 10N |

Description
Note:

Delivery time: 35 calendar days

Minimum order quantity: 3 pcs.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 371

Thread pitch: 0.7 mm

Overall length L: 63 mm

Shank \varnothing D_s: 4.5 mm

Shank square \square : 3.4 mm

Tapping hole \varnothing : 3.3 mm

Technical description

| | |
|---------------------------|---------|
| Number of cutting edges Z | 3 |
| Tool material | HSS E |
| Number of clamping slots | 3 |
| Thread pitch | 0.7 mm |
| Standard | DIN 371 |
| Overall length L | 63 mm |
| Thread \varnothing | 4 mm |
| Thread depth | 8 mm |

| | |
|----------------------------------|--|
| Shank $\varnothing D_s$ | 4.5 mm |
| Shank square \square | 3.4 mm |
| Tapping hole \varnothing | 3.3 mm |
| Thread type | M/MF |
| Thread size | M4×0.7 |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | B |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for through holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for conventional machining |
| Colour ring | without |
| Type of product | Tap |