

Garant
Through hole machine tap, uncoated, M: M50X2

Order data

Order number	130000 M50X2
GTIN	4045197625588
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: M/MF
 Tool material: HSS E
 Standard: DIN 376
 Thread pitch: 2 mm
 Overall length L: 250 mm
 Shank $\varnothing D_s$: 40 mm
 Shank square \square : 32 mm
 Tapping hole \varnothing : 48 mm

Technical description

Shank $\varnothing D_s$	40 mm
Standard	DIN 376
Tapping hole \varnothing	48 mm
Number of cutting edges Z	4
Overall length L	250 mm
Shank square \square	32 mm
Thread pitch	2 mm
Thread \varnothing	50 mm

Number of clamping slots	4
Tool material	HSS E
Thread depth	100 mm
Thread type	M/MF
Thread size	M50×2
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap