

Garant**Through hole machine tap, uncoated, M: M50X3****Order data**

Order number	130000 M50X3
GTIN	4045197625595
Item class	10N

Description**Note:**

Delivery time: 35 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 376

Thread pitch: 3 mm

Overall length L: 250 mm

Shank Ø D_s: 40 mm

Shank square □: 32 mm

Tapping hole Ø: 47 mm

Technical description

Shank square □	32 mm
Thread pitch	3 mm
Standard	DIN 376
Shank Ø D _s	40 mm
Thread Ø	50 mm
Number of clamping slots	4
Number of cutting edges Z	4
Overall length L	250 mm

Thread depth	100 mm
Tapping hole Ø	47 mm
Tool material	HSS E
Thread type	M/MF
Thread size	M50×3
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap