

Garant
Through hole machine tap, uncoated, M: M51X0,75

Order data

Order number	130000 M51X0,75
GTIN	4045197625625
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: M/MF
 Tool material: HSS E
 Standard: DIN 376
 Thread pitch: 0.75 mm
 Overall length L: 250 mm
 Shank \varnothing D_s: 40 mm
 Shank square □: 32 mm
 Tapping hole \varnothing : 50.25 mm

Technical description

Number of clamping slots	4
Thread \varnothing	51 mm
Thread pitch	0.75 mm
Shank square □	32 mm
Standard	DIN 376
Tool material	HSS E
Tapping hole \varnothing	50.25 mm
Thread depth	102 mm

Overall length L	250 mm
Number of cutting edges Z	4
Shank $\varnothing D_s$	40 mm
Thread type	M/MF
Thread size	M51 \times 0.75
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3 \times D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap