

**Garant****Through hole machine tap, uncoated, M: M7X0,35****Order data**

|              |                |
|--------------|----------------|
| Order number | 130000 M7X0,35 |
| GTIN         | 4045197997883  |
| Item class   | 10N            |

**Description****Note:**

Delivery time: 35 calendar days

Minimum order quantity: 3 pcs.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 371

Thread pitch: 0.35 mm

Overall length L: 80 mm

Shank Ø D<sub>s</sub>: 7 mm

Shank square □: 5.5 mm

Tapping hole Ø: 6.65 mm

**Technical description**

|                          |         |
|--------------------------|---------|
| Tool material            | HSS E   |
| Number of clamping slots | 3       |
| Shank square □           | 5.5 mm  |
| Thread Ø                 | 7 mm    |
| Thread depth             | 14 mm   |
| Overall length L         | 80 mm   |
| Shank Ø D <sub>s</sub>   | 7 mm    |
| Thread pitch             | 0.35 mm |

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Tapping hole Ø                   | 6.65 mm                                |
| Standard                         | DIN 371                                |
| Number of cutting edges Z        | 3                                      |
| Thread type                      | M/MF                                   |
| Thread size                      | M7×0.35                                |
| Coating                          | uncoated                               |
| Flank angle                      | 60 degrees                             |
| Thread standard                  | DIN 13                                 |
| Taper lead form                  | B                                      |
| Shank                            | Plain shank with h9                    |
| Through-coolant                  | no                                     |
| Application for type of drilling | up to 3×D for through holes            |
| Cutting direction                | right-hand                             |
| Type of threading tool           | Machine tap for conventional machining |
| Colour ring                      | without                                |
| Type of product                  | Tap                                    |