

Garant
Through hole machine tap, uncoated, M: M8X0,35

Order data

Order number	130000 M8X0,35
GTIN	4045197997920
Item class	10N

Description
Note:

Delivery time: 35 calendar days

Minimum order quantity: 3 pcs.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 371

Thread pitch: 0.35 mm

Overall length L: 90 mm

Shank $\varnothing D_s$: 8 mm

Shank square \square : 6.2 mm

Tapping hole \varnothing : 7.65 mm

Technical description

Standard	DIN 371
Overall length L	90 mm
Number of clamping slots	3
Tapping hole \varnothing	7.65 mm
Shank $\varnothing D_s$	8 mm
Thread pitch	0.35 mm
Thread depth	16 mm
Shank square \square	6.2 mm

Tool material	HSS E
Number of cutting edges Z	3
Thread Ø	8 mm
Thread type	M/MF
Thread size	M8×0.35
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap