Garant

Left-hand thread through hole machine tap, uncoated, MF: M10X0,35



Order data

Order number	130001 M10X0,35
GTIN	4062406000806
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 3 pcs.
Special / custom-made product - return not possible
Thread type: M/MF-LH
Tool material: HSS E
Standard: DIN 371
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 0.35 mm
Overall length L: 100 mm
Shank ∅ D_s: 10 mm
Shank square □: 8 mm
Tapping hole ∅: 9.65 mm

Technical description

Thread depth	20 mm
Number of clamping slots	3
Shank ∅ D_s	10 mm
Tool material	HSS E
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX

Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tolerance class	6H +0.20
Shank square ☐	8 mm
Tapping hole ⌀	9.65 mm
Thread pitch	0.35 mm
Number of cutting edges Z	3
Thread ⌀	10 mm
Standard	DIN 371
Overall length L	100 mm
Thread type	M/MF-LH
Thread size	M10×0.35
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap