

Garant**Left-hand thread through hole machine tap, uncoated, MF: M32X1,75****Order data**

Order number	130001 M32X1,75
GTIN	4062406002527
Item class	10N

Description**Note:**

Delivery time: 35 calendar days
Minimum order quantity: 1 pc.
Special / custom-made product - return not possible
Thread type: M/MF-LH
Tool material: HSS E
Standard: DIN 376
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 1.75 mm
Overall length L: 180 mm
Shank \varnothing D_s: 25 mm
Shank square \square : 20 mm
Tapping hole \varnothing : 30.25 mm

Technical description

Tapping hole \varnothing	30.25 mm
Standard	DIN 376
Tool material	HSS E
Thread depth	64 mm
Overall length L	180 mm
Tolerance class	ISO 1 4H

Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tolerance class	6H +0.20
Number of clamping slots	4
Shank square □	20 mm
Number of cutting edges Z	4
Thread pitch	1.75 mm
Thread Ø	32 mm
Shank Ø D _s	25 mm
Thread type	M/MF-LH
Thread size	M32×1.75
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining

Colour ring

without

Type of product

Tap