

**Garant****Left-hand thread through hole machine tap, uncoated, MF: M3X0,35****Order data**

|              |                |
|--------------|----------------|
| Order number | 130001 M3X0,35 |
| GTIN         | 4062406000479  |
| Item class   | 10N            |

**Description****Note:**

Delivery time: 35 calendar days

Minimum order quantity: 3 pcs.

Special / custom-made product - return not possible

Thread type: M/MF-LH

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 0.35 mm

Overall length L: 56 mm

Shank Ø D<sub>s</sub>: 3.5 mm

Shank square □: 2.7 mm

Tapping hole Ø: 2.65 mm

**Technical description**

|                           |            |
|---------------------------|------------|
| Standard                  | DIN 371    |
| Number of clamping slots  | 3          |
| Number of cutting edges Z | 3          |
| Tolerance class           | ISO 1 4H   |
| Tolerance class           | ISO 1X 4HX |
| Tolerance class           | ISO 2 6H   |

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Tolerance class                  | ISO 2X 6HX                             |
| Tolerance class                  | 6H +0.05                               |
| Tolerance class                  | ISO 3 6G                               |
| Tolerance class                  | ISO 3X 6GX                             |
| Tolerance class                  | 7H                                     |
| Tolerance class                  | 7HX                                    |
| Tolerance class                  | 7G                                     |
| Tolerance class                  | 7GX                                    |
| Tolerance class                  | 6H +0.10                               |
| Tolerance class                  | 6H +0.20                               |
| Overall length L                 | 56 mm                                  |
| Thread Ø                         | 3 mm                                   |
| Tapping hole Ø                   | 2.65 mm                                |
| Shank square □                   | 2.7 mm                                 |
| Shank Ø D <sub>s</sub>           | 3.5 mm                                 |
| Thread depth                     | 6 mm                                   |
| Tool material                    | HSS E                                  |
| Thread pitch                     | 0.35 mm                                |
| Thread type                      | M/MF-LH                                |
| Thread size                      | M3×0.35                                |
| Coating                          | uncoated                               |
| Flank angle                      | 60 degrees                             |
| Thread standard                  | DIN 13                                 |
| Taper lead form                  | B                                      |
| Shank                            | Plain shank with h9                    |
| Through-coolant                  | no                                     |
| Application for type of drilling | up to 3×D for through holes            |
| Cutting direction                | left-hand                              |
| Type of threading tool           | Machine tap for conventional machining |

|                 |         |
|-----------------|---------|
| Colour ring     | without |
| Type of product | Tap     |