Garant

Through hole machine tap, TiN, MF: M12X0,35

Order data

Order number	130005 M12X0,35
GTIN	4062406004491
Item class	10N

Description

Note:
Delivery time: 49 calendar days
Minimum order quantity: 2 pcs.
Special / custom-made product - return not possible
Thread type: M/MF
Tool material: HSS E
Standard: DIN 376
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 0.35 mm
Overall length L: 110 mm
Shank ∅ D_s: 9 mm
Shank square ☐: 7 mm
Tapping hole ∅: 11.65 mm

Technical description

Number of cutting edges Z	3
Thread ∅	12 mm
Thread pitch	0.35 mm
Tapping hole ∅	11.65 mm
Number of clamping slots	3
Overall length L	110 mm

Standard	DIN 376
Shank square ☐	7 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tolerance class	6H +0.20
Shank ∅ D_s	9 mm
Thread depth	24 mm
Tool material	HSS E
Thread type	M/MF
Thread size	M12×0.35
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap