

Garant
Through hole machine tap, TiN, MF: M23X0,35

Order data

Order number	130005 M23X0,35
GTIN	4062406005351
Item class	10N

Description
Note:

Delivery time: 49 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: M/MF
 Tool material: HSS E
 Standard: DIN 376
 Tolerance class: ISO 1 4H
 Tolerance class: ISO 1X 4HX
 Tolerance class: ISO 2 6H
 Thread pitch: 0.35 mm
 Overall length L: 160 mm
 Shank \varnothing D_s: 18 mm
 Shank square □: 14.5 mm
 Tapping hole \varnothing : 22.65 mm

Technical description

Tool material	HSS E
Number of clamping slots	3
Thread pitch	0.35 mm
Overall length L	160 mm
Thread depth	46 mm
Thread \varnothing	23 mm

Tapping hole \varnothing	22.65 mm
Standard	DIN 376
Shank square \square	14.5 mm
Shank $\varnothing D_s$	18 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tolerance class	6H +0.20
Number of cutting edges Z	3
Thread type	M/MF
Thread size	M23x0.35
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3xD for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring

without

Type of product

Tap