Garant

Left-hand thread through hole machine tap, TiN, MF: M13X1,25

Order data

Order number	130006 M13X1,25
GTIN	4062406008178
Item class	10N

Description

Note:
Delivery time: 49 calendar days
Minimum order quantity: 2 pcs.
Special / custom-made product - return not possible
Thread type: M/MF-LH
Tool material: HSS E
Standard: DIN 376
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 1.25 mm
Overall length L: 110 mm
Shank ⌀ D_s: 11 mm
Shank square ☐: 9 mm
Tapping hole ⌀: 11.75 mm

Technical description

Tool material	HSS E
Tapping hole ⌀	11.75 mm
Thread ⌀	13 mm
Standard	DIN 376
Shank ⌀ D_s	11 mm
Thread pitch	1.25 mm

Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Thread depth	26 mm
Overall length L	110 mm
Shank square ☐	9 mm
Number of cutting edges Z	3
Number of clamping slots	3
Thread type	M/MF-LH
Thread size	M13×1.25
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap