

**Garant****Left-hand thread through hole machine tap, TiN, MF: M35X0,75****Order data**

|              |                 |
|--------------|-----------------|
| Order number | 130006 M35X0,75 |
| GTIN         | 4062406009878   |
| Item class   | 10N             |

**Description****Note:**

Delivery time: 49 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF-LH

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 0.75 mm

Overall length L: 200 mm

Shank Ø D<sub>s</sub>: 28 mm

Shank square □: 22 mm

Tapping hole Ø: 34.25 mm

**Technical description**

|                          |         |
|--------------------------|---------|
| Standard                 | DIN 376 |
| Number of clamping slots | 4       |
| Overall length L         | 200 mm  |
| Tool material            | HSS E   |
| Thread pitch             | 0.75 mm |
| Thread depth             | 70 mm   |

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Tapping hole Ø                   | 34.25 mm                               |
| Shank Ø D <sub>s</sub>           | 28 mm                                  |
| Thread Ø                         | 35 mm                                  |
| Tolerance class                  | ISO 1 4H                               |
| Tolerance class                  | ISO 1X 4HX                             |
| Tolerance class                  | ISO 2 6H                               |
| Tolerance class                  | ISO 2X 6HX                             |
| Tolerance class                  | 6H +0.05                               |
| Tolerance class                  | 6H +0.20                               |
| Tolerance class                  | ISO 3 6G                               |
| Tolerance class                  | ISO 3X 6GX                             |
| Tolerance class                  | 7H                                     |
| Tolerance class                  | 7HX                                    |
| Tolerance class                  | 7G                                     |
| Tolerance class                  | 7GX                                    |
| Tolerance class                  | 6H +0.10                               |
| Number of cutting edges Z        | 4                                      |
| Shank square □                   | 22 mm                                  |
| Thread type                      | M/MF-LH                                |
| Thread size                      | M35×0.75                               |
| Coating                          | TiN                                    |
| Flank angle                      | 60 degrees                             |
| Thread standard                  | DIN 13                                 |
| Taper lead form                  | B                                      |
| Shank                            | Plain shank with h9                    |
| Through-coolant                  | no                                     |
| Application for type of drilling | up to 3×D for through holes            |
| Cutting direction                | left-hand                              |
| Type of threading tool           | Machine tap for conventional machining |

|                 |         |
|-----------------|---------|
| Colour ring     | without |
| Type of product | Tap     |