

**Garant**
**Left-hand thread through hole machine tap, TiN, MF: M36X1,5**

**Order data**

|              |                |
|--------------|----------------|
| Order number | 130006 M36X1,5 |
| GTIN         | 4062406009977  |
| Item class   | 10N            |

**Description**
**Note:**

Delivery time: 49 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF-LH

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 1.5 mm

Overall length L: 200 mm

Shank  $\varnothing D_s$ : 28 mm

Shank square  $\square$ : 22 mm

Tapping hole  $\varnothing$ : 34.5 mm

**Technical description**

|                          |        |
|--------------------------|--------|
| Tool material            | HSS E  |
| Shank $\varnothing D_s$  | 28 mm  |
| Shank square $\square$   | 22 mm  |
| Number of clamping slots | 4      |
| Overall length L         | 200 mm |
| Thread pitch             | 1.5 mm |

|                                  |  |
|----------------------------------|--|
| Thread Ø                         | 36 mm                                  |
| Tapping hole Ø                   | 34.5 mm                                |
| Standard                         | DIN 376                                |
| Number of cutting edges Z        | 4                                      |
| Thread depth                     | 72 mm                                  |
| Tolerance class                  | ISO 1 4H                               |
| Tolerance class                  | ISO 1X 4HX                             |
| Tolerance class                  | ISO 2 6H                               |
| Tolerance class                  | ISO 2X 6HX                             |
| Tolerance class                  | 6H +0.05                               |
| Tolerance class                  | 6H +0.20                               |
| Tolerance class                  | ISO 3 6G                               |
| Tolerance class                  | ISO 3X 6GX                             |
| Tolerance class                  | 7H                                     |
| Tolerance class                  | 7HX                                    |
| Tolerance class                  | 7G                                     |
| Tolerance class                  | 7GX                                    |
| Tolerance class                  | 6H +0.10                               |
| Thread type                      | M/MF-LH                                |
| Thread size                      | M36×1.5                                |
| Coating                          | TiN                                    |
| Flank angle                      | 60 degrees                             |
| Thread standard                  | DIN 13                                 |
| Taper lead form                  | B                                      |
| Shank                            | Plain shank with h9                    |
| Through-coolant                  | no                                     |
| Application for type of drilling | up to 3×D for through holes            |
| Cutting direction                | left-hand                              |
| Type of threading tool           | Machine tap for conventional machining |

|                 |         |
|-----------------|---------|
| Colour ring     | without |
| Type of product | Tap     |