Garant

Spiral flute machine tap, uncoated, MF: M15X1,75



Order data

Order number	130010 M15X1,75
GTIN	4062406011925
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 2 pcs.
Special / custom-made product - return not possible
Thread type: M/MF
Tool material: HSS E
Standard: DIN 376
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 1.75 mm
Overall length L: 110 mm
Shank ∅ D_s: 12 mm
Shank square ☐: 9 mm
Tapping hole ∅: 13.25 mm

Technical description

Tapping hole ∅	13.25 mm
Thread pitch	1.75 mm
Thread ∅	15 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H

Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tool material	HSS E
Number of cutting edges Z	3
Shank ⌀ D_s	12 mm
Shank square ☐	9 mm
Standard	DIN 376
Thread depth	30 mm
Number of clamping slots	3
Overall length L	110 mm
Thread type	M/MF
Thread size	M15×1.75
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap