

Garant
Spiral flute machine tap, uncoated, M: M1X0,2

Order data

Order number	130010 M1X0,2
GTIN	4045197625892
Item class	10N

Description
Note:

Delivery time: 91 calendar days

Minimum order quantity: 25 pcs.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 371

Thread pitch: 0.2 mm

Overall length L: 40 mm

Shank $\varnothing D_s$: 2.5 mm

Shank square \square : 2.1 mm

Tapping hole \varnothing : 0.8 mm

Technical description

Thread depth	2 mm
Thread pitch	0.2 mm
Number of clamping slots	2
Overall length L	40 mm
Shank square \square	2.1 mm
Thread \varnothing	1 mm
Shank $\varnothing D_s$	2.5 mm
Tool material	HSS E

Tapping hole Ø	0.8 mm
Number of cutting edges Z	2
Standard	DIN 371
Thread type	M/MF
Thread size	M1×0.2
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap