

**Garant**
**Spiral flute machine tap, uncoated, MF: M3X0,35**

**Order data**

Order number	130010 M3X0,35
GTIN	4062406011185
Item class	10N

**Description**
**Note:**

Delivery time: 35 calendar days  
 Minimum order quantity: 3 pcs.  
 Special / custom-made product - return not possible  
 Thread type: M/MF  
 Tool material: HSS E  
 Standard: DIN 371  
 Tolerance class: ISO 1 4H  
 Tolerance class: ISO 1X 4HX  
 Tolerance class: ISO 2 6H  
 Thread pitch: 0.35 mm  
 Overall length L: 56 mm  
 Shank  $\varnothing D_s$ : 3.5 mm  
 Shank square  $\square$ : 2.7 mm  
 Tapping hole  $\varnothing$ : 2.65 mm

**Technical description**

Thread $\varnothing$	3 mm
Number of clamping slots	3
Shank $\varnothing D_s$	3.5 mm
Overall length L	56 mm
Thread pitch	0.35 mm
Number of cutting edges Z	3

Tool material	HSS E
Standard	DIN 371
Thread depth	6 mm
Shank square □	2.7 mm
Tapping hole Ø	2.65 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Thread type	M/MF
Thread size	M3×0.35
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap