

Garant**Left-hand thread blind hole machine tap, uncoated, MF: M1,1X0,2****Order data**

| | |
|--------------|-----------------|
| Order number | 130011 M1,1X0,2 |
| GTIN | 4062406014537 |
| Item class | 10N |

Description**Note:**

Delivery time: 91 calendar days

Minimum order quantity: 25 pcs.

Special / custom-made product - return not possible

Thread type: M/MF-LH

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 0.2 mm

Overall length L: 40 mm

Shank $\varnothing D_s$: 2.5 mmShank square \square : 2.1 mmTapping hole \varnothing : 0.9 mm**Technical description**

| | |
|--------------------------|------------|
| Tool material | HSS E |
| Thread depth | 2.2 mm |
| Number of clamping slots | 2 |
| Tolerance class | ISO 1 4H |
| Tolerance class | ISO 1X 4HX |
| Tolerance class | ISO 2 6H |

| | |
|----------------------------------|--|
| Tolerance class | ISO 2X 6HX |
| Tolerance class | 6H +0.05 |
| Tolerance class | 6H +0.20 |
| Tolerance class | ISO 3 6G |
| Tolerance class | ISO 3X 6GX |
| Tolerance class | 7H |
| Tolerance class | 7HX |
| Tolerance class | 7G |
| Tolerance class | 7GX |
| Tolerance class | 6H +0.10 |
| Shank square □ | 2.1 mm |
| Overall length L | 40 mm |
| Shank Ø D _s | 2.5 mm |
| Standard | DIN 371 |
| Tapping hole Ø | 0.9 mm |
| Number of cutting edges Z | 2 |
| Thread pitch | 0.2 mm |
| Thread Ø | 1.1 mm |
| Thread type | M/MF-LH |
| Thread size | M1.1×0.2 |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | C |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 2.5×D for blind holes |
| Cutting direction | left-hand |
| Type of threading tool | Machine tap for conventional machining |

| | |
|-----------------|---------|
| Colour ring | without |
| Type of product | Tap |