

Garant
Left-hand thread blind hole machine tap, uncoated, MF: M10X0,75

Order data

Order number	130011 M10X0,75
GTIN	4062406015145
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 3 pcs.
 Special / custom-made product - return not possible
 Thread type: M/MF-LH
 Tool material: HSS E
 Standard: DIN 371
 Tolerance class: ISO 1 4H
 Tolerance class: ISO 1X 4HX
 Tolerance class: ISO 2 6H
 Thread pitch: 0.75 mm
 Overall length L: 100 mm
 Shank $\varnothing D_s$: 10 mm
 Shank square \square : 8 mm
 Tapping hole \varnothing : 9.25 mm

Technical description

Shank square \square	8 mm
Overall length L	100 mm
Number of clamping slots	3
Tool material	HSS E
Shank $\varnothing D_s$	10 mm
Standard	DIN 371

Tapping hole Ø	9.25 mm
Thread pitch	0.75 mm
Thread depth	20 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Thread Ø	10 mm
Number of cutting edges Z	3
Thread type	M/MF-LH
Thread size	M10×0.75
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap