Garant

Left-hand thread blind hole machine tap, uncoated, MF: M17X1,25

Order data

Order number	130011 M17X1,25
GTIN	4062406015657
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 2 pcs.
Special / custom-made product - return not possible
Thread type: M/MF-LH
Tool material: HSS E
Standard: DIN 376
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 1.25 mm
Overall length L: 125 mm
Shank ∅ D_s: 14 mm
Shank square ☐: 11 mm
Tapping hole ∅: 15.75 mm

Technical description

Thread ∅	17 mm
Shank square ☐	11 mm
Standard	DIN 376
Overall length L	125 mm
Tool material	HSS E
Shank ∅ D_s	14 mm

Number of cutting edges Z	3
Tapping hole ∅	15.75 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Thread pitch	1.25 mm
Thread depth	34 mm
Number of clamping slots	3
Thread type	M/MF-LH
Thread size	M17×1.25
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap