

**Garant****Spiral flute machine tap, TiN, MF: M27X1,75****Order data**

Order number	130015 M27X1,75
GTIN	4062406020071
Item class	10N

**Description****Note:**

Delivery time: 49 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 376

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 1.75 mm

Overall length L: 160 mm

Shank  $\varnothing$  D<sub>s</sub>: 20 mm

Shank square  $\square$ : 16 mm

Tapping hole  $\varnothing$ : 25.25 mm

**Technical description**

Thread pitch	1.75 mm
Tool material	HSS E
Standard	DIN 376
Overall length L	160 mm
Thread depth	54 mm
Tapping hole $\varnothing$	25.25 mm

Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Thread $\varnothing$	27 mm
Shank square $\square$	16 mm
Number of cutting edges Z	4
Shank $\varnothing D_s$	20 mm
Number of clamping slots	4
Thread type	M/MF
Thread size	M27×1.75
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap