

Garant**Spiral flute machine tap, TiN, MF: M9X0,35****Order data**

Order number	130015 M9X0,35
GTIN	4062406018672
Item class	10N

Description**Note:**

Delivery time: 49 calendar days

Minimum order quantity: 3 pcs.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS E

Standard: DIN 371

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 0.35 mm

Overall length L: 90 mm

Shank Ø D_s: 9 mm

Shank square □: 7 mm

Tapping hole Ø: 8.65 mm

Technical description

Shank square □	7 mm
Tool material	HSS E
Thread depth	18 mm
Thread pitch	0.35 mm
Number of clamping slots	3
Overall length L	90 mm

Thread Ø	9 mm
Shank Ø D _s	9 mm
Tapping hole Ø	8.65 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Number of cutting edges Z	3
Standard	DIN 371
Thread type	M/MF
Thread size	M9×0.35
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining

Colour ring

without

Type of product

Tap