Garant

Left-hand thread blind hole machine tap, TiN, MF: M2X0,35



Order data

Order number	130016 M2X0,35
GTIN	4062406021887
Item class	10N

Description

Note:
Delivery time: 91 calendar days
Minimum order quantity: 25 pcs.
Special / custom-made product - return not possible
Thread type: M/MF-LH
Tool material: HSS E
Standard: DIN 371
Tolerance class: ISO 1 4H
Tolerance class: ISO 1X 4HX
Tolerance class: ISO 2 6H
Thread pitch: 0.35 mm
Overall length L: 45 mm
Shank ∅ D_s: 2.8 mm
Shank square □: 2.1 mm
Tapping hole ∅: 1.65 mm

Technical description

Number of clamping slots	3
Number of cutting edges Z	3
Shank ∅ D_s	2.8 mm
Overall length L	45 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX

Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.05
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.10
Tool material	HSS E
Tapping hole ⌀	1.65 mm
Standard	DIN 371
Shank square ☐	2.1 mm
Thread ⌀	2 mm
Thread pitch	0.35 mm
Thread depth	4 mm
Thread type	M/MF-LH
Thread size	M2×0.35
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining

Colour ring	without
Type of product	Tap