

**Garant**
**Machine tap for through holes and blind holes, uncoated, M: M53X0,5**

**Order data**

Order number	130020 M53X0,5
GTIN	4045197625939
Item class	10N

**Description**
**Note:**

Delivery time: 35 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS

Standard: DIN 2184

Thread pitch: 0.5 mm

Overall length L: 140 mm

Shank  $\varnothing$  D<sub>s</sub>: 40 mm

Shank square  $\square$ : 32 mm

Tapping hole  $\varnothing$ : 52.5 mm

**Technical description**

Thread depth	79.5 mm
Tool material	HSS
Tapping hole $\varnothing$	52.5 mm
Shank square $\square$	32 mm
Thread $\varnothing$	53 mm
Standard	DIN 2184
Number of clamping slots	6
Overall length L	140 mm

Shank $\varnothing D_s$	40 mm
Number of cutting edges Z	6
Thread pitch	0.5 mm
Thread type	M/MF
Thread size	M53×0.5
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap