

Garant
Left-hand thread through hole and blind hole machine tap, uncoated, MF: M110X1

Order data

| | |
|--------------|---------------|
| Order number | 130021 M110X1 |
| GTIN | 4062406029487 |
| Item class | 10N |

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: M/MF-LH
 Tool material: HSS
 Standard: DIN 2184
 Tolerance class: ISO 1 4H
 Tolerance class: ISO 1X 4HX
 Tolerance class: ISO 2 6H
 Thread pitch: 1 mm
 Overall length L: 180 mm
 Shank \varnothing D_s: 56 mm
 Shank square \square : 44 mm
 Tapping hole \varnothing : 109 mm

Technical description

| | |
|----------------------------|--------|
| Tool material | HSS |
| Number of clamping slots | 12 |
| Number of cutting edges Z | 12 |
| Tapping hole \varnothing | 109 mm |
| Thread depth | 165 mm |

| | |
|----------------------------------|---|
| Shank $\varnothing D_s$ | 56 mm |
| Thread \varnothing | 110 mm |
| Thread pitch | 1 mm |
| Tolerance class | ISO 1 4H |
| Tolerance class | ISO 1X 4HX |
| Tolerance class | ISO 2 6H |
| Tolerance class | ISO 2X 6HX |
| Tolerance class | 6H +0.20 |
| Tolerance class | ISO 3 6G |
| Tolerance class | ISO 3X 6GX |
| Tolerance class | 7H |
| Tolerance class | 7HX |
| Tolerance class | 7G |
| Tolerance class | 7GX |
| Tolerance class | 6H +0.05 |
| Tolerance class | 6H +0.10 |
| Overall length L | 180 mm |
| Shank square \square | 44 mm |
| Standard | DIN 2184 |
| Thread type | M/MF-LH |
| Thread size | M110×1 |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | DIN 13 |
| Taper lead form | C |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 1.5×D for blind holes and through holes |
| Cutting direction | left-hand |

| | |
|------------------------|--|
| Type of threading tool | Machine tap for conventional machining |
| Colour ring | without |
| Type of product | Tap |