

**Garant****Left-hand thread through hole and blind hole machine tap, uncoated, MF: M65X2****Order data**

Order number	130021 M65X2
GTIN	4062406028145
Item class	10N

**Description****Note:**

Delivery time: 35 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF-LH

Tool material: HSS

Standard: DIN 2184

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 2 mm

Overall length L: 160 mm

Shank  $\varnothing$  D<sub>s</sub>: 50 mmShank square  $\square$ : 39 mmTapping hole  $\varnothing$ : 63 mm**Technical description**

Standard	DIN 2184
Tapping hole $\varnothing$	63 mm
Thread pitch	2 mm
Overall length L	160 mm
Thread $\varnothing$	65 mm

Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.05
Tolerance class	6H +0.10
Number of clamping slots	6
Thread depth	97.5 mm
Shank square □	39 mm
Shank $\varnothing D_s$	50 mm
Number of cutting edges Z	6
Tool material	HSS
Thread type	M/MF-LH
Thread size	M65×2
Coating	uncoated
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	left-hand

Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap