

Garant**Machine tap for through holes and blind holes, TiN, MF: M56X1,5****Order data**

Order number	130025 M56X1,5
GTIN	4062406029890
Item class	10N

Description**Note:**

Delivery time: 49 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: M/MF

Tool material: HSS

Standard: DIN 2184

Tolerance class: ISO 1 4H

Tolerance class: ISO 1X 4HX

Tolerance class: ISO 2 6H

Thread pitch: 1.5 mm

Overall length L: 140 mm

Shank Ø D_s: 40 mm

Shank square □: 32 mm

Tapping hole Ø: 54.5 mm

Technical description

Shank square □	32 mm
Standard	DIN 2184
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX

Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.05
Tolerance class	6H +0.10
Overall length L	140 mm
Shank Ø D _s	40 mm
Tool material	HSS
Number of clamping slots	6
Thread Ø	56 mm
Thread depth	84 mm
Tapping hole Ø	54.5 mm
Number of cutting edges Z	6
Thread pitch	1.5 mm
Thread type	M/MF
Thread size	M56×1.5
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	right-hand

Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap