

Garant
**Left-hand thread through hole and blind hole machine tap, TiN, MF:
M102X0,75**

Order data

Order number	130026 M102X0,75
GTIN	4062406033729
Item class	10N

Description
Note:

Delivery time: 49 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: M/MF-LH
 Tool material: HSS
 Standard: DIN 2184
 Tolerance class: ISO 1 4H
 Tolerance class: ISO 1X 4HX
 Tolerance class: ISO 2 6H
 Thread pitch: 0.75 mm
 Overall length L: 180 mm
 Shank \varnothing D_s: 56 mm
 Shank square \square : 44 mm
 Tapping hole \varnothing : 101.25 mm

Technical description

Number of clamping slots	12
Number of cutting edges Z	12
Tapping hole \varnothing	101.25 mm
Standard	DIN 2184
Thread depth	153 mm

Thread Ø	102 mm
Shank Ø D _s	56 mm
Tolerance class	ISO 1 4H
Tolerance class	ISO 1X 4HX
Tolerance class	ISO 2 6H
Tolerance class	ISO 2X 6HX
Tolerance class	6H +0.20
Tolerance class	ISO 3 6G
Tolerance class	ISO 3X 6GX
Tolerance class	7H
Tolerance class	7HX
Tolerance class	7G
Tolerance class	7GX
Tolerance class	6H +0.05
Tolerance class	6H +0.10
Overall length L	180 mm
Thread pitch	0.75 mm
Shank square □	44 mm
Tool material	HSS
Thread type	M/MF-LH
Thread size	M102×0.75
Coating	TiN
Flank angle	60 degrees
Thread standard	DIN 13
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 1.5×D for blind holes and through holes
Cutting direction	left-hand

Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap