

Garant**Through hole machine tap, uncoated, Type: 2-4,5****Order data**

Order number	130030 2-4,5
GTIN	4062406036478
Item class	10N

Description**Note:**

Delivery time: 35 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: UNC

Tool material: HSS E

Standard: DIN 376

Thread Ø: 50.8 mm

Overall length L: 250 mm

Shank Ø D_s: 40 mm

Shank square □: 32 mm

Tapping hole Ø: 45.03 mm

Technical description

Thread pitch	5.644 mm
Number of clamping slots	4
Tool material	HSS E
Standard	DIN 376
Overall length L	250 mm
Tapping hole Ø	45.03 mm
Number of cutting edges Z	4
Shank square □	32 mm

Thread depth	101.6 mm
Shank Ø D _s	40 mm
Thread Ø	50.8 mm
Thread type	UNC
Thread size	2-4,5 UNC
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap