

Garant
Through hole machine tap, uncoated, Type: 5/8-11

Order data

| | |
|--------------|---------------|
| Order number | 130030 5/8-11 |
| GTIN | 4062406035082 |
| Item class | 10N |

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 2 pcs.
 Special / custom-made product - return not possible
 Thread type: UNC
 Tool material: HSS E
 Standard: DIN 376
 Threads per inch: 11
 Thread \varnothing : 15.875 mm
 Overall length L: 110 mm
 Shank \varnothing D_s: 12 mm
 Shank square \square : 9 mm
 Tapping hole \varnothing : 13.53 mm

Technical description

| | |
|------------------------------------|----------|
| Shank \varnothing D _s | 12 mm |
| Shank square \square | 9 mm |
| Number of clamping slots | 3 |
| Tapping hole \varnothing | 13.53 mm |
| Overall length L | 110 mm |
| Thread depth | 31.75 mm |
| Thread pitch | 2.309 mm |
| Tool material | HSS E |

| | |
|----------------------------------|--|
| Number of cutting edges Z | 3 |
| Threads per inch | 11 |
| Thread Ø | 15.875 mm |
| Standard | DIN 376 |
| Thread type | UNC |
| Thread size | 5/8-11 UNC |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | ASME B1.1 |
| Tolerance class | 1B |
| Tolerance class | 2B +0.20 |
| Tolerance class | 2B +0.10 |
| Tolerance class | 3B |
| Tolerance class | 2B |
| Tolerance class | 2B +0.05 |
| Taper lead form | B |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 3×D for through holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for conventional machining |
| Colour ring | without |
| Type of product | Tap |