Garant

Through hole machine tap, uncoated, Type: 7/16-18



Order data

Order number	130030 7/16-18
GTIN	4062406034825
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 2 pcs.
Special / custom-made product - return not possible
Thread type: UNS
Tool material: HSS E
Standard: DIN 376
Threads per inch: 18
Thread ∅: 11.112 mm
Overall length L: 110 mm
Shank ∅ D_s: 9 mm
Shank square ☐: 7 mm
Tapping hole ∅: 9.75 mm

Technical description

Tapping hole ∅	9.75 mm
Thread ∅	11.112 mm
Shank square ☐	7 mm
Shank ∅ D_s	9 mm
Thread pitch	1.411 mm
Tool material	HSS E
Thread depth	22.224 mm
Threads per inch	18

Number of clamping slots	3
Overall length L	110 mm
Standard	DIN 376
Number of cutting edges Z	3
Thread type	UNS
Thread size	7/16-18 UNS
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap