

Garant**Through hole machine tap, uncoated, Type: 7/8-20****Order data**

Order number	130030 7/8-20
GTIN	4062406035266
Item class	10N

Description**Note:**

Delivery time: 35 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: UNEF

Tool material: HSS E

Standard: DIN 376

Threads per inch: 20

Thread Ø: 22.225 mm

Overall length L: 140 mm

Shank Ø D_s: 18 mm

Shank square □: 14.5 mm

Tapping hole Ø: 21.15 mm

Technical description

Standard	DIN 376
Thread Ø	22.225 mm
Thread pitch	1.27 mm
Tool material	HSS E
Shank square □	14.5 mm
Tapping hole Ø	21.15 mm
Threads per inch	20
Number of cutting edges Z	3

Number of clamping slots	3
Thread depth	44.45 mm
Overall length L	140 mm
Shank Ø D _s	18 mm
Thread type	UNEF
Thread size	7/8-20 UNEF
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap