

Garant
Left-hand thread through hole machine tap, uncoated, Type: 1-10

Order data

Order number	130031 1-10
GTIN	4062406037673
Item class	10N

Description
Note:

Delivery time: 35 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: UNS-LH

Tool material: HSS E

Standard: DIN 376

Threads per inch: 10

Thread Ø: 25.4 mm

Overall length L: 160 mm

Shank Ø D_s: 20 mm

Shank square □: 16 mm

Tapping hole Ø: 23 mm

Technical description

Tapping hole Ø	23 mm
Overall length L	160 mm
Tool material	HSS E
Thread depth	50.8 mm
Standard	DIN 376
Thread pitch	2.54 mm
Thread Ø	25.4 mm
Shank square □	16 mm

Number of cutting edges Z	4
Shank $\varnothing D_s$	20 mm
Threads per inch	10
Number of clamping slots	4
Thread type	UNS-LH
Thread size	1-10 UNS LH
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap