

Garant
Left-hand thread through hole machine tap, uncoated, Type: 15/16-16

Order data

Order number	130031 15/16-16
GTIN	4062406037581
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 1 pc.
 Special / custom-made product - return not possible
 Thread type: UN-LH
 Tool material: HSS E
 Standard: DIN 376
 Threads per inch: 16
 Thread \varnothing : 23.812 mm
 Overall length L: 160 mm
 Shank \varnothing D_s: 18 mm
 Shank square \square : 14.5 mm
 Tapping hole \varnothing : 22.3 mm

Technical description

Number of clamping slots	3
Thread \varnothing	23.812 mm
Tapping hole \varnothing	22.3 mm
Thread pitch	1.588 mm
Standard	DIN 376
Tool material	HSS E
Shank square \square	14.5 mm
Threads per inch	16

Overall length L	160 mm
Number of cutting edges Z	3
Thread depth	47.624 mm
Shank $\varnothing D_s$	18 mm
Thread type	UN-LH
Thread size	15/16-16 UN LH
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	B
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 3×D for through holes
Cutting direction	left-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap