

**Garant**
**Left-hand thread through hole machine tap, TiN, Type: 2-20**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 130036 2-20   |
| GTIN         | 4062406043124 |
| Item class   | 10N           |

**Description**
**Note:**

Delivery time: 49 calendar days

Minimum order quantity: 1 pc.

Special / custom-made product - return not possible

Thread type: UN-LH

Tool material: HSS E

Standard: DIN 376

Threads per inch: 20

Thread  $\varnothing$ : 50.8 mm

Overall length L: 250 mm

Shank  $\varnothing$  D<sub>s</sub>: 40 mm

Shank square  $\square$ : 32 mm

Tapping hole  $\varnothing$ : 49.58 mm

**Technical description**

|                                    |          |
|------------------------------------|----------|
| Tapping hole $\varnothing$         | 49.58 mm |
| Tool material                      | HSS E    |
| Thread $\varnothing$               | 50.8 mm  |
| Threads per inch                   | 20       |
| Shank $\varnothing$ D <sub>s</sub> | 40 mm    |
| Thread pitch                       | 1.27 mm  |
| Overall length L                   | 250 mm   |
| Number of cutting edges Z          | 4        |

|                                  |  |
|----------------------------------|--|
| Thread depth                     | 101.6 mm                               |
| Standard                         | DIN 376                                |
| Number of clamping slots         | 4                                      |
| Shank square □                   | 32 mm                                  |
| Thread type                      | UN-LH                                  |
| Thread size                      | 2-20 UN LH                             |
| Coating                          | TiN                                    |
| Flank angle                      | 60 degrees                             |
| Thread standard                  | ASME B1.1                              |
| Tolerance class                  | 1B                                     |
| Tolerance class                  | 2B +0.20                               |
| Tolerance class                  | 2B +0.10                               |
| Tolerance class                  | 3B                                     |
| Tolerance class                  | 2B                                     |
| Tolerance class                  | 2B +0.05                               |
| Taper lead form                  | B                                      |
| Shank                            | Plain shank with h9                    |
| Through-coolant                  | no                                     |
| Application for type of drilling | up to 3×D for through holes            |
| Cutting direction                | left-hand                              |
| Type of threading tool           | Machine tap for conventional machining |
| Colour ring                      | without                                |
| Type of product                  | Tap                                    |