

Garant**Blind hole machine tap, uncoated, Type: 11/16-24****Order data**

Order number	130040 11/16-24
GTIN	4062406044053
Item class	10N

Description**Note:**

Delivery time: 35 calendar days

Minimum order quantity: 2 pcs.

Special / custom-made product - return not possible

Thread type: UNEF

Tool material: HSS E

Standard: DIN 376

Threads per inch: 24

Thread Ø: 17.462 mm

Overall length L: 125 mm

Shank Ø D_s: 14 mm

Shank square □: 11 mm

Tapping hole Ø: 16.6 mm

Technical description

Thread depth	34.924 mm
Tapping hole Ø	16.6 mm
Standard	DIN 376
Number of cutting edges Z	4
Thread pitch	1.058 mm
Overall length L	125 mm
Number of clamping slots	4
Shank Ø D _s	14 mm

Shank square ☐	11 mm
Thread Ø	17.462 mm
Tool material	HSS E
Threads per inch	24
Thread type	UNEF
Thread size	11/16-24 UNEF
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap