

**Garant**
**Blind hole machine tap, uncoated, Type: 5/8-16**

**Order data**

Order number	130040 5/8-16
GTIN	4062406044015
Item class	10N

**Description**
**Note:**

Delivery time: 35 calendar days  
 Minimum order quantity: 2 pcs.  
 Special / custom-made product - return not possible  
 Thread type: UN  
 Tool material: HSS E  
 Standard: DIN 376  
 Threads per inch: 16  
 Thread  $\varnothing$ : 15.875 mm  
 Overall length L: 110 mm  
 Shank  $\varnothing$  D<sub>s</sub>: 12 mm  
 Shank square  $\square$ : 9 mm  
 Tapping hole  $\varnothing$ : 14.4 mm

**Technical description**

Thread depth	31.75 mm
Thread $\varnothing$	15.875 mm
Tapping hole $\varnothing$	14.4 mm
Tool material	HSS E
Number of cutting edges Z	3
Thread pitch	1.588 mm
Threads per inch	16
Overall length L	110 mm

Shank $\varnothing D_s$	12 mm
Shank square $\square$	9 mm
Standard	DIN 376
Number of clamping slots	3
Thread type	UN
Thread size	5/8-16 UN
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap