

Garant
Blind hole machine tap, uncoated, Type: 7/16-28

Order data

Order number	130040 7/16-28
GTIN	4062406043742
Item class	10N

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 2 pcs.
 Special / custom-made product - return not possible
 Thread type: UNEF
 Tool material: HSS E
 Standard: DIN 376
 Threads per inch: 28
 Thread \varnothing : 11.112 mm
 Overall length L: 110 mm
 Shank $\varnothing D_s$: 9 mm
 Shank square \square : 7 mm
 Tapping hole \varnothing : 10.35 mm

Technical description

Thread \varnothing	11.112 mm
Threads per inch	28
Number of cutting edges Z	3
Tool material	HSS E
Thread depth	22.224 mm
Thread pitch	0.907 mm
Shank $\varnothing D_s$	9 mm
Standard	DIN 376

Tapping hole Ø	10.35 mm
Shank square □	7 mm
Number of clamping slots	3
Overall length L	110 mm
Thread type	UNEF
Thread size	7/16-28 UNEF
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap