

Garant
Blind hole machine tap, uncoated, Type: 7/16-32

Order data

| | |
|--------------|----------------|
| Order number | 130040 7/16-32 |
| GTIN | 4062406192969 |
| Item class | 10N |

Description
Note:

Delivery time: 28 calendar days

Minimum order quantity: 2 pcs.

Special / custom-made product - return not possible

Thread type: UNS

Tool material: HSS E

Standard: DIN 376

Threads per inch: 32

Thread \varnothing : 11.112 mm

Overall length L: 110 mm

Shank \varnothing D_s: 9 mm

Shank square \square : 7 mm

Tapping hole \varnothing : 10.4 mm

Technical description

| | |
|------------------------------------|-----------|
| Thread \varnothing | 11.112 mm |
| Shank \varnothing D _s | 9 mm |
| Number of clamping slots | 3 |
| Tool material | HSS E |
| Threads per inch | 32 |
| Thread depth | 27.78 mm |
| Shank square \square | 7 mm |
| Overall length L | 110 mm |

| | |
|----------------------------------|--|
| Tapping hole Ø | 10.4 mm |
| Standard | DIN 376 |
| Number of cutting edges Z | 3 |
| Thread pitch | 0.794 mm |
| Thread type | UNS |
| Thread size | 7/16-32 UNS |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | ASME B1.1 |
| Taper lead form | C |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 2.5×D for blind holes |
| Cutting direction | right-hand |
| Type of threading tool | Machine tap for conventional machining |
| Colour ring | without |
| Type of product | Tap |