Garant

Blind hole machine tap, uncoated, Type: 9/16-20

Order data

Order number	130040 9/16-20
GTIN	4062406043926
Item class	10N

Description

Note:
Delivery time: 35 calendar days
Minimum order quantity: 2 pcs.
Special / custom-made product - return not possible
Thread type: UN
Tool material: HSS E
Standard: DIN 376
Threads per inch: 20
Thread ∅: 14.288 mm
Overall length L: 110 mm
Shank ∅ D_s: 11 mm
Shank square ☐: 9 mm
Tapping hole ∅: 13.1 mm

Technical description

Threads per inch	20
Number of cutting edges Z	3
Shank square ☐	9 mm
Thread ∅	14.288 mm
Number of clamping slots	3
Shank ∅ D_s	11 mm
Tapping hole ∅	13.1 mm
Thread pitch	1.27 mm

Tool material	HSS E
Thread depth	28.576 mm
Standard	DIN 376
Overall length L	110 mm
Thread type	UN
Thread size	9/16-20 UN
Coating	uncoated
Flank angle	60 degrees
Thread standard	ASME B1.1
Tolerance class	1B
Tolerance class	2B +0.20
Tolerance class	2B +0.10
Tolerance class	3B
Tolerance class	2B
Tolerance class	2B +0.05
Taper lead form	C
Shank	Plain shank with h9
Through-coolant	no
Application for type of drilling	up to 2.5×D for blind holes
Cutting direction	right-hand
Type of threading tool	Machine tap for conventional machining
Colour ring	without
Type of product	Tap