

Garant
Left-hand thread blind hole machine tap, uncoated, Type: 1/4-48

Order data

| | |
|--------------|---------------|
| Order number | 130041 1/4-48 |
| GTIN | 4062406045739 |
| Item class | 10N |

Description
Note:

Delivery time: 35 calendar days
 Minimum order quantity: 3 pcs.
 Special / custom-made product - return not possible
 Thread type: UNS-LH
 Tool material: HSS E
 Standard: DIN 371
 Threads per inch: 48
 Thread \varnothing : 6.35 mm
 Overall length L: 80 mm
 Shank \varnothing D_s: 7 mm
 Shank square \square : 5.5 mm
 Tapping hole \varnothing : 5.85 mm

Technical description

| | |
|------------------------------------|---------|
| Number of cutting edges Z | 3 |
| Number of clamping slots | 3 |
| Tapping hole \varnothing | 5.85 mm |
| Thread depth | 12.7 mm |
| Threads per inch | 48 |
| Shank \varnothing D _s | 7 mm |
| Standard | DIN 371 |
| Overall length L | 80 mm |

| | |
|----------------------------------|--|
| Thread pitch | 0.529 mm |
| Thread Ø | 6.35 mm |
| Tool material | HSS E |
| Shank square □ | 5.5 mm |
| Thread type | UNS-LH |
| Thread size | 1/4-48 UNS LH |
| Coating | uncoated |
| Flank angle | 60 degrees |
| Thread standard | ASME B1.1 |
| Tolerance class | 1B |
| Tolerance class | 2B +0.20 |
| Tolerance class | 2B +0.10 |
| Tolerance class | 3B |
| Tolerance class | 2B |
| Tolerance class | 2B +0.05 |
| Taper lead form | C |
| Shank | Plain shank with h9 |
| Through-coolant | no |
| Application for type of drilling | up to 2.5×D for blind holes |
| Cutting direction | left-hand |
| Type of threading tool | Machine tap for conventional machining |
| Colour ring | without |
| Type of product | Tap |